

The CMS Detector *Status and Prospects*

Jeremiah Mans

On behalf of the CMS Collaboration

APS April Meeting --- April 14, 2007



A Compact Muon Solenoid




- Philosophy:

“At the core of the CMS detector sits a large superconducting solenoid generating a uniform magnetic field of 4 T. The choice of a strong magnetic field leads to a compact design for...”

C.M.S.

A Compact Solenoidal Detector for L.H.C.




- Single long solenoid magnet containing calorimeters and inner tracker
- Muon momentum measurement performed using return flux from solenoid passing through a barrel and endcap iron yoke.



CMS Solenoid



Magnetic length	12.5 m
Free bore diameter	6 m
Central magnetic induction	4 T $\approx 100,000$ times earth magnetic field
Temperature	4.2 degrees Kelvin
Nominal current	20 kA
Stored energy	2.7 GJ
Magnetic Radial Pressure	64 Atmospheres



Magnet History




April 14, 2007

The CMS Detector: Status and Prospects

Testing the Magnet


300 K



4 K



19kA (220806)



Dump Resistor for CMS Magnet



Not a magnet alone...

SUPERCONDUCTING COIL

CALORIMETERS

ECAL

Scintillating PbWO₄ crystals

HCAL

Plastic scintillator/brass sandwich

IRON YOKE

TRACKER

Silicon Microstrips
Pixels

Total weight : 12,500 t
Overall diameter : 15 m
Overall length : 21.6 m
Magnetic field : 4 Tesla


MUON BARREL

Drift Tube Chambers (**DT**)


Resistive Plate Chambers (**RPC**)

MUON ENDCAPS

Cathode Strip Chambers (**CSC**)
Resistive Plate Chambers (**RPC**)



The Cosmic Challenge



- The magnet test period was also a test for the detectors: sections of all subdetectors participated in a “cosmic challenge”

- Shakedown test
 - Installation/commissioning
 - Operations
 - Working as a combined detector



MTCC Outcome in a single slide




Statistics


~ 230 million events
written to tape

~ 41 million events
at full field

~ 50 million events
with all
subdetectors (1M
at full field)



The Muon Systems




Central ($|\eta| < 1.2$)



- Drift Tubes (DT)
- Barrel Resistive Plate Chambers (RPC)

Endcaps ($0.9 < |\eta| < 2.4$)

- Cathode Strip Chambers (CSC)
- Endcap RPCs




Commissioning





- Commissioning and operation of the muon chambers began in 2004 with the operation of the first CSCs installed on the iron.
- Both the CSCs and DTs operated successfully in local mode well before beginning the Cosmic Challenge


Trigger Synchronization




- MTCC was a *more* challenging environment for synchronization than LHC
 - Cosmic muons are not synchronized to the LHC clock!
 - Cosmic muons don't come from the center of the detector!



Cosmic Challenge Results



CMS All-Silicon Tracker




207m² of silicon sensors
10.6 million silicon strips
65.9 million pixels ~ 1.1 m²

The Pixel Tracker



- Partial installation of pixel system expected in 2007, full system in 2008.



April 14, 2007




The CMS Detector: Status and Prospects




CMS Silicon Strip Tracker



TOB (Outer Barrel)




TIB (Inner Barrel)



TID (Inner Disks)




TEC (EndCap)




Tracker Integration




TEC+ Insertion




Tracker at MTCC






- A small section of the tracker was inserted for the first period of MTCC
- Provided both operational and mechanical integration practice
- ~9000 tracks reconstructed in MTCC dataset



The Calorimeters of CMS





The CMS Electromagnetic Calorimeter




Barrel: Avalanche Photodiode (APD)
Gain ~ 50
QE ~ 70%





Endcap: Vacuum Phototriode
Gain ~ 10
QE ~ 20%
Radiation Hard



HCAL Segmentation and Coverage




Layer to Tower Decoding Fiber





Forward Calorimeters

Zero-Degree Calorimeter



HF





100 GeV
electron

100 GeV
pion

Hadronic section important for CMS Heavy Ion program
EM section important for diffractive and forward physics


Calorimeters at MTCC



HCAL – triggered cosmic muon







2 SMs inserted Apr 06 for magnet tests



Testbeam Proving Ground


H4



The Trigger and DAQ Systems




- CMS is designed with only one level of hardware trigger.
- The events are read out and built using mostly commodity networking hardware at an event rate of 100 kHz.
- Software-based “High-Level Trigger” provides filtering down to O(100 Hz)



Into the Cavern





- The CMS integration plan has always envisioned the assembly of the detector on the surface, followed by lowering into the experimental cavern.



1994 Technical Design



CMS Descending...



April 14, 2007

The CMS Detector: Status and Prospects


Lowering the Magnet



April 14, 2007

The CMS Detector: Status and Prospects


CMS Today (actually 2 weeks ago)




April 14, 2007

The CMS Detector: Status and Prospects

Installation and Commissioning



HF Pedestal RMS Values






HF Pedestal RMS Values	
Entries	1644
Mean	0.9098
RMS	0.03885


April 14, 2007

The CMS Detector: Status and Prospects


The Payoff



Precision measurements (e.g top)



Higgs!



SUSY?



QGP?

